

# 'U STÙCCU

D048 Plaster-based smoothing paste stucco for high-quality finishes



## DESCRIPTION

'U STÙCCU is a gypsum-based paste formulated with ultrafine-grained fillers and high-quality Sicilian gypsum crystals. It ensures excellent filling power, a high level of whiteness, and exceptionally easy sanding.

'U STÙCCU does not tear during application and guarantees extreme smoothness.

'U STÙCCU It is indicated for use on gypsum or cement-based plasters, allowing fillings up to 8 mm in multiple layers.

## APPLICATION

'USTÙCCU should be applied to intact, dry, clean, and compact surfaces, free of flaking patches and free of moisture stains, dirt, grease, or similar residues. Any old, loose or dusty paint should be removed by brushing or sanding the substrate.

Use **DOC PRIMER** with a dilution ratio of 1:2 with water using a roller or brush to the substrate, once it dries (refer D014 MTDS for drying time and other technical details) spread out 'U STÙCCU using a roller and let it soak for a while to penetrate into the substrate and flatten it using a long metal spatula, apply several coats until the surface is perfectly even. It's recommended to hold the paint under a light to spot even the smallest irregularities or depressions. Once dry, proceed with sanding using 120-grit sandpaper.

## STORAGE

'U STÙCCU maintains its properties for up-to 18months, if protected from excessive heat and cold. To maintain its effectiveness, store in its original, sealed packaging in a cool, dry area away from direct sunlight, heat, and moisture. Storage temperature must be between +5°C and +30°C.

**KEEP FROM FREEZING**

## SAFETY GUIDELINES

Avoid contact with skin and eyes. In case of contact, rinse thoroughly with water. For further information, see the safety data sheet.

## DISPOSAL

The material must be disposed of in accordance with local regulations. Empty plastic containers can be recycled or sent to recycling facilities.

## 'USTÙCCU TECHNICAL TABLE

Aspect	Viscous paste
Colour	Matt white
Packaging	5KG 20KG
Tools	Roller, Metallic spatula
Specific Gravity	1,60 ± 0,02 Kg/l
Theoretical yield	1,6 kg/m <sup>2</sup> x mm thick
Touch dry	6 hours a 20°C
Dry to overcoat	24 hours a 20°C
Dry residue	71 ± 0,5 %
HS CODE	32141090

The information provided is based on our experience and technical and scientific knowledge; however, we cannot be held responsible for the results obtained using these products, as the application conditions are beyond our control. It is always advisable to ensure that the product is suitable for each specific use.

Document

MTDS048ENG

Issuing date

14.10.25

Revision

-



Designed and manufactured entirely in Italy

sales@decora-ac.com